

# MTH

- **STONE CRUSHER**
- **ROCK GRINDER**
- **STABILIZER**
- **ASPHALT SHREDDER**

FOR TRACTORS **FROM 300 TO 400 HP** WITH MAXIMUM WORKING DEPTH OF **50 CM** AND **VARIABLE GEOMETRY CRUSHING CHAMBER**.

The MTH is the top of the multipurpose machines line, used to grind rock slabs, crush stones, shred asphalt and stabilize soil, with a maximum working depth of 50 cm. A specially designed gear transmission allows the rotor to work constantly at optimum speeds. The variable geometry crushing chamber is a leading-edge design solution to ensure optimum crushing results. The mobile rotor, which can be hydraulically adjusted from the trac-

tor cab, allows the volume of the crushing chamber to increase according to the working depth. Limited traction stress means reduced fuel consumption, increased operating speed and therefore, the ability to save time and operating costs. The HARDOX® counter knife and rear-mounted grill system ensure that the final product is the correct size.



MODEL	Tractor (min/max)	PDF (rpm)	Working width (mm)	Total width (mm)	Weight (kg)	ROTOR G/3		ROTOR R		No. teeth/type R + R/HD + STC/3/FP + STC/FP	
						Working depth (mm)		Working depth (mm)			
						Max. 1	Max. 2	Max. 1	Max. 2		
MTH 200	300-400	1000	2080	2600	6900	350	500	104+4+4	340	500	138+24+6+6
MTH 225	300-400	1000	2320	2840	7200	350	500	116+4+4	340	500	160+24+6+6

Max.1: with rotor only Max.2: maximum depth  
This information refers to the machine equipped as standard. The technical data in this catalogue may be altered without prior notice.



## ABSOLUTE EXCELLENCE



### TOUGH

WELDOX® steel frame and guards in made of HARDOX® steel to ensure the utmost resistance to wear and tear.



### PRODUCTIVITY

Technological excellence meets maximum power to ensure superior performance.



### EFFICIENCY

The variable geometry crushing chamber, protected by HARDOX® covering, ensures excellent grinding results.



### PRECISION

The HARDOX® counter knife and rear-mounted grill system ensure that the final product is the correct size.